

HMIS Rating		MATERIAL SAFETY DATA SHEET (Complies with OSHA Communication Standard 29 CFR 1910.1200 Dept. of Labor) Form approved OMB No. 1218-0072 OSHA 174 - Sept. 1985	NFPA Rating	
Health	1		Health	1
Flammability	4		Flammability	4
Reactivity	0		Reactivity	0
Personal Protection	B		Special	0

Section I - Product Identification

Hang Time

74155

Marketer's Name Must Appear Below	DOT Shipping and Hazard Classification Consumer Commodity ORM-D
Manufactured For: Maintenance Magic	Emergency Telephone Number 1 (800) 255-3924
Address: 740 Clay St. N.W. Auburn, WA 98001	Telephone Number for Information (253) 804-8666
	Date Prepared 10/04/95

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, CAS Number)	OSHA PEL	ACGIH TLV	STEL	% Wt. (Approx.)
<p>The specific chemical identities of the ingredients of this mixture are considered to be trade secrets and are in accordance with the provisions of section 1910:1200 of Title 29 of the Code of Federal Regulations</p> <p style="text-align: center;">CAS: NJ TSRN 240TR</p>				

All chemical compounds marked with an Asterisk () are toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372. You must notify each person to whom this mixture or trade name is sold. This statement must remain a part of this Material Safety Data Sheet.*

Section III - Physical/Chemical Characteristics

Boiling Point: NA	Specific Gravity (H ₂ O=1): <1	Melting Point: N/A
Vapor Pressure PSIG @ 70°F: 70	Vapor Density (Air=1): NE	Evaporation Rate (Butyl Acetate=1): NE
Solubility in Water: Soluble	Appearance: Clear liquid	Odor: Fragrance

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used): NA	NON-FLAMMABLE	Flammable Limits: LEL UEL NE NE
Extinguishing Media: Foam, dry chemical, carbon dioxide, water.		
Special Fire Fighting Procedures: Provide shielding for personnel. Wear self-contained breathing apparatus. Cool containers with water fog to prevent rupturing and spewing.		
Unusual Fire and Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.		

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in this MSDS. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

Section V - Reactivity Data		
STABILITY:	<input type="checkbox"/> Unstable <input checked="" type="checkbox"/> Stable	Conditions to Avoid: High temperatures.
Incompatibility (Materials To Avoid): Alkalis, oxidizing materials, amines		
Hazardous Decomposition or By-products: CO, CO2		
Hazardous Polymerization	<input type="checkbox"/> May Occur <input checked="" type="checkbox"/> Will Not Occur	Conditions to Avoid: Open flame, welding arcs, heat.
Section VI - Health Hazard Data		
Routes of Entry: Inhalation Yes Ingestion Skin Absorption Eye		
Carcinogenicity: NTP? IARC Monograph? OSHA Regulated?		
Health Hazards (Acute and Chronic): Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness. Eye and skin irritant. Possible chemical pneumonitis if aspirated into lungs. Nausea. CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of the mixture): May cause cardiac abnormality, liver abnormalities, kidney and/or lung damage.		
Signs and Symptoms of Exposure		
Inhalation:	Difficulty in breathing	
Ingestion:	Nausea and vomiting.	
Skin Contact:	Redness.	
Eye Contact:	Irritation.	
Medical Conditions Aggravated by Exposure: May aggravate existing eye, skin or upper respiratory conditions.		
Emergency First Aid Procedures		
Inhalation:	Remove to fresh air. Give oxygen. Resuscitate if necessary. Get medical help.	
Ingestion:	DO NOT INDUCE VOMITING. Drink 2 large glasses of water. Get medical help immediately.	
Skin Contact:	Wash with soap and water. If irritated, see a physician.	
Eye Contact:	Flush with water for 15 minutes. If irritated see a physician.	
Section VII - Precautions for Safe Handling and Use		
Steps to be Taken in Case Material is Released or Spilled:	Absorb with suitable medium. Incinerate or landfill according to local, state or federal regulations. DO NOT FLUSH TO SEWER.	
Waste Disposal Method:	Aerosol cans when vented to atmospheric pressure through normal use, pose no hazard	
Precautions to be Taken in Handling and Storing:	Do not puncture or incinerate containers. Do not store at temperatures above 130°F	
Other Precautions:	KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors. Remove ignition sources.	
Section VIII - Control Measures		
Protective Equipment Types		
Eyes:	Safety glasses recommended.	
Respiratory:	If vapor concentration exceeds TLV, use respirator approved by U.S. Bureau of mines for organic vapor.	
Gloves:	Latex if skin is easily irritated.	
Other:	None	
Ventilation:	General Mechanical	Local Exhaust Yes Other
Work/Hygienic Practises:	Wash with soap and water before handling food. Remove contaminated clothing.	