

<b>HMIS Rating</b>		<b>MATERIAL SAFETY DATA SHEET</b> (Complies with OSHA Communication Standard 29 CFR 1910.1200 Dept. of Labor) Form approved OMB No. 1218-0072 OSHA 174 - Sept. 1985	<b>NFPA Rating</b>	
Health	<b>1</b>		Health	<b>1</b>
Flammability	<b>1</b>		Flammability	<b>1</b>
Reactivity	<b>0</b>		Reactivity	<b>0</b>

### Section I - Product Identification

## RTV White - Gasket Sealer and Maker 74128

Marketer's Name Must Appear Below	DOT Shipping and Hazard Classification <b>Consumer Commodity ORM-D</b>
Manufactured For: <b>Maintenance Magic</b>	24 Hour Emergency Response: <b>1 (800) 255-3924</b>
Address: <b>740 Clay St. N.W. Auburn, WA 98001</b>	Telephone Number for Information <b>(253) 804-8666</b>
	Date Prepared <b>10/13/93</b>

### Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, CAS Number)	OSHA PEL	ACGIH TLV	SARA III
<b>Silica, Amorphous</b> 7631-86-9	<b>6mg/m3</b>	<b>10mg/m3</b>	<b>NO</b>
<b>Methyltriacetoxysilane</b> 4253-34-3	<b>10</b>	<b>10</b>	<b>NO</b>
<b>Ethyltriacetoxysilane</b> 17689-77-9	<b>10</b>	<b>10</b>	<b>NO</b>

*All chemical compounds marked with an Asterisk (\*) are toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372. You must notify each person to whom this mixture or trade name is sold. This statement must remain a part of this Material Safety Data Sheet.*

### Section III - Physical/Chemical Characteristics

Boiling Point: <b>NA</b>	Specific Gravity (H <sub>2</sub> O=1): <b>1.03</b>	Melting Point: <b>NA</b>
Vapor Pressure PSIG @ 70°F: <b>NA</b>	Vapor Density (Air=1): <b>NA</b>	Evaporation Rate (Butyl Acetate=1): <b>NA</b>
Solubility in Water: <b>&lt;0.1</b>	Appearance: <b>White paste</b>	Odor: <b>acetic acid-like odor</b>

### Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) <b>NA</b>	Flammability as per Flame Projection Test: <b>NA</b>	Flammable Limits: LEL UEL <b>ND ND</b>
Extinguishing Media: <b>Use water, water fog, dry chemical or carbon dioxide, foam</b>		
Special Fire Fighting Procedures: <b>Self-contained breathing apparatus &amp; protective clothing should be worn.</b>		
Unusual Fire and Explosion Hazards: <b>Containers may rupture if heated above 130°F</b>		

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in this MSDS. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

<b>Section V - Reactivity Data</b>		
STABILITY:	<input type="checkbox"/> Unstable <input checked="" type="checkbox"/> Stable	Conditions to Avoid: <b>High temperatures.</b>
Incompatibility (Materials To Avoid): <b>Oxidizing materials. Air or moisture causes curing &amp; acetic acid vapors form</b>		
Hazardous Decomposition or By-products: Metal oxides, silicon dioxide, carbon dioxide, traces of incompletely burned carbon products, includes formaldehyde		
Hazardous Polymerization	<input type="checkbox"/> May Occur <input checked="" type="checkbox"/> Will Not Occur	Conditions to Avoid: <b>Exposure to air or moisture until ready to use</b>
<b>Section VI - Health Hazard Data</b>		
<b>Routes of Entry:</b> Inhalation <b>Yes</b> Ingestion    Skin Absorption    Eye		
<b>Carcinogenicity:</b> NTP?    IARC Monograph?    OSHA Regulated? <b>Not presently on any list.</b>		
<b>Health Hazards (Acute and Chronic):</b> None known.		
<b>Signs and Symptoms of Exposure</b>		
<b>Inhalation:</b>	Vapor overexposure may irritate nose and throat.	
<b>Ingestion:</b>	Swallowing large amounts may cause serious injury.	
<b>Skin Contact:</b>	Short exposure may irritate. Repeated prolonged contact may irritate moderately.	
<b>Eye Contact:</b>	Direct contact irritates slightly with swelling and redness.	
Medical Conditions Aggravated by Exposure: <b>Nose, throat, skin and digestive system.</b>		
<b>Emergency First Aid Procedures</b>		
<b>Inhalation:</b>	Remove to fresh air. If ill effects persist, get medical attention.	
<b>Ingestion:</b>	DO NOT INDUCE VOMITING. Drink lg qty of water. Get immediate medical attention.	
<b>Skin Contact:</b>	Wipe off & flush with water. If irritation develops, get medical attention.	
<b>Eye Contact:</b>	Flush with water for 15 minutes. Get medical attention.	
<b>Section VII - Precautions for Safe Handling and Use</b>		
Steps to be Taken in Case Material is Released or Spilled:	Remove product and contain for salvage or disposal. <b>Dispose as hazardous waste in accordance with local, state &amp; federal laws.</b>	
Waste Disposal Method:	<b>Keep away from heat, sparks or open flame. Store at temperatures below 90°F.</b>	
Precautions to be Taken in Handling and Storing:	<b>KEEP OUT OF REACH OF CHILDREN.</b> Product forms acetic acid when exposed to water or humid air. Provide ventilation during use to control acetic acid exposure limits within 10ppm.	
Other Precautions:	<b>When spraying more than one half can continuously or more than one can consecutively, use NIOSH approved respirator.</b>	
<b>Section VIII - Control Measures</b>		
Protective Equipment Types		
Eyes:	<b>Safety glasses.</b>	
Respiratory:	<b>None needed.</b>	
Gloves:	<b>Rubber or plastic.</b>	
Other:	<b>Long sleeve and long pants.</b>	
Ventilation:	General Mechanical    Local Exhaust <b>Yes</b> Other	
Work/Hygienic Practises: <b>Remove contaminated clothing and shoes and clean thoroughly before reuse.</b>		