

HMIS Rating		<b>MATERIAL SAFETY DATA SHEET</b> (Complies with OSHA Communication Standard 29 CFR 1910.1200 Dept. of Labor) Form approved OMB No. 1218-0072 OSHA 174 - Sept. 1985	NFPA Rating	
Health	X		Health	X
Flammability	X		Flammability	X
Reactivity	X		Reactivity	X
Personal Protection			Special	

**Section I - Product Identification**

## Tool Ease 74172

Marketer's Name Must Appear Below	DOT Shipping and Hazard Classification Consumer Commodity ORM-D
Manufactured For: <b>Maintenance Magic</b>	Emergency Telephone Number <b>1-800-255-3294</b>
Address: <b>740 Clay St. N.W. Auburn, WA 98001</b>	Telephone Number for Information <b>(253) 804-8666</b>
	Date Prepared 12/21/96

**Section II - Hazardous Ingredients/Identity Information**

Hazardous Components (Specific Chemical Identity, CAS Number)	OSHA PEL	ACGIH TLV	STEL	% Wt. (Approx.)
Specific information is considered as a trade secret and is withheld per CEF 1910:1200 (h). Medical personnel requiring this information should contact Maintenance Magic with their request per CER 1010:1200 (h).				

*All chemical compounds marked with an Asterisk (\*) are toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372. You must notify each person to whom this mixture or trade name is sold. This statement must remain a part of this Material Safety Data Sheet.*

**Section III - Physical/Chemical Characteristics**

Boiling Point: 409.0 F @ 15 mmHg	Specific Gravity (H <sub>2</sub> O=1): .810 @ 60.0 F / .848 @ 77.0 F	Melting Point:
Vapor Pressure PSIG @ 70°F: N/A	Vapor Density (Air=1): N/A	Evaporation Rate (Butyl Acetate=1): >1.0
Solubility in Water: Insoluble	Appearance: homogeneous solution, clear	Odor: L color 5Y 0.5R MAX

**Section IV - Fire and Explosion Hazard Data**

Flash Point (Method Used): 200°F PMCC	Flammable Limits: LEL UEL N/A
Extinguishing Media: Use water fog, dry chemical or foam.	
Special Fire Fighting Procedures: By product of combustion: May form carbon dioxide and carbon monoxide.	
Unusual Fire and Explosion Hazards: None	

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in this MSDS. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

<b>Section V - Reactivity Data</b>			
STABILITY:	<input type="checkbox"/> Unstable	Conditions to Avoid:	
	<input checked="" type="checkbox"/> Stable	Strong oxidizing agents and strong mineral acids.	
Incompatibility (Materials To Avoid): Strong oxidizing agents and strong mineral acids.			
Hazardous Decomposition or By-products: May form carbon dioxide and carbon monoxide.			
Hazardous Polymerization	<input type="checkbox"/> May Occur	Conditions to Avoid:	
	<input checked="" type="checkbox"/> Will Not Occur	Strong oxidizing agents and strong mineral acids.	
<b>Section VI - Health Hazard Data</b>			
<b>Routes of Entry:</b> Inhalation Yes    Ingestion Yes    Skin Absorption Yes    Eye Yes			
<b>Carcinogenicity:</b> NTP?    IARC Monograph?    OSHA Regulated?    No			
<b>Health Hazards (Acute and Chronic):</b> No exposure limits have been set for this product. As with all industrial materials, exposure of this product to the skin and eyes should be avoided. This product (or components, if a mixture) is not listed in IRAC, the NPT Third Annual Report as a carcinogen or a potential carcinogen. It is not regulated by OSHA as a carcinogen.			
<b>Signs and Symptoms of Exposure</b>			
<b>Inhalation:</b>	Difficulty in breathing		
<b>Ingestion:</b>	Nausea and vomiting.		
<b>Skin Contact:</b>	Redness.		
<b>Eye Contact:</b>	Irritation.		
Medical Conditions Aggravated by Exposure:			
<b>Emergency First Aid Procedures</b>			
<b>Inhalation:</b>	Remove from area of exposure, seek medical attention of symptoms persist.		
<b>Ingestion:</b>	If swallowed seek medical attention. Induce vomiting. Do not leave unattended.		
<b>Skin Contact:</b>	Wash with soap and water.		
<b>Eye Contact:</b>	Flush with large amounts of water, lifting upper and lower lids occasionally.		
<b>Section VII - Precautions for Safe Handling and Use</b>			
Steps to be Taken in Case Material is Released or Spilled:	Remove sources of ignition, contain spill. Stop leakage. Pick up small spills with absorbent materials. Recover large spills for salvage or disposal. Wash hard surfaces with safety solvent or detergent to remove remaining oil film.		
Waste Disposal Method:	Follow local, state, and federal disposal regulations.		
Precautions to be Taken in Handling and Storing:	Store in closed containers below 120°F. Keep away from oxidizing agents, excessive heat & ignition sources. Use in well ventilated areas. Drum is not a pressure vessel.		
Other Precautions:	Do not store or use near heat, sparks & flame; store out of sun. Do not puncture, drag, or incinerate container.		
<b>Section VIII - Control Measures</b>			
Protective Equipment Types			
Eyes:	Safety glasses, goggles or face shield recommended to protect eyes from mists or splashing.		
Respiratory:	Not required under normal conditions of use.		
Gloves:	Neoprene or rubber gloves recommended to prevent skin contact.		
Other:	Practice good personal hygiene, washing exposed areas of skin and contaminated clothing.		
Ventilation:	General Mechanical	Local Exhaust Yes	Other
Work/Hygienic Practises: Do not smoke while using. Wash hands after use.			