Safety Data Sheet



Revision Number: 008.0 Issue date: 06/25/2020

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE SI 5015 BL known as Loctite(R) Superflex(R) Blue R

Product type/use: Sealant Restriction of Use: None identified

Company address: Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

IDH number: 270639

Item number:30533Region:United States

Contact information:

Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711

1-877-671-4608 (toll free) of 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW			
WARNING:	CAUSES SKIN IRRITATION.		
	CAUSES SERIOUS EYE IRRITATION.		

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A

PICTOGRAM(S)



Precautionary Statements

IDH number: 270639

Prevention: Wash affected area thoroughly after handling. Wear protective gloves, eye protection, and face

protection

Response: IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off

contaminated clothing.

Storage: Not prescribed Disposal: Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Silicon dioxide	7631-86-9	5 - 10
29H,31H-phthalocyaninato(2-)- N29,N30,N31,N32 copper	147-14-8	1 - 5
Methylsilanetriyl triacetate	4253-34-3	0.1 - 1
Triacetoxyethylsilane	17689-77-9	0.1 - 1
Gamma-glycidoxypropyl trimethoxysilane	2530-83-8	0.1 - 1

^{*} Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

Product name: LOCTITE SI 5015 BL known as Loctite(R) Superflex(R) Blue R Page 1 of 5

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. If symptoms develop and persist, get medical attention.

Skin contact: Wipe off with paper towel or cloth. Wash with soap and water. If skin irritation

persists, call a physician.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Get medical attention.

Ingestion: DO NOT induce vomiting unless directed to do so by medical personnel.

Never give anything by mouth to an unconscious person. Get medical

attention.

Symptoms: See Section 11.

Notes to physician: Treat symptomatically.

5. FIRE FIGHTING MEASURES

Extinguishing media: Foam, dry chemical or carbon dioxide.

Special firefighting procedures: None
Unusual fire or explosion hazards: None

Hazardous combustion products: Acrid smoke and fumes. Silica mist. Formaldehyde.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Maintain good ventilation for large spills. Scrape up as much material as

possible. Spilled material will solidify. Store in a partly filled, closed container

until disposal.

7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Prevent contact with eyes, skin and

clothing. Do not breathe vapor and mist. Wash thoroughly after handling.

Storage: For safe storage, store at or below 90 °F (32.2 °C)

Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Silicon dioxide	6 mg/m3 TWA	20 MPPCF TWA 0.8 mg/m3 TWA	None	3 mg/m3 TWA Respirable fraction.
29H,31H-phthalocyaninato(2-)- N29,N30,N31,N32 copper	0.2 mg/m3 TWA (as Cu) Fume. 1 mg/m3 TWA (as Cu) Dust and mist.	None	None	None
Methylsilanetriyl triacetate	None	None	None	None
Triacetoxyethylsilane	None	None	None	None
Gamma-glycidoxypropyl trimethoxysilane	None	None	None	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

IDH number: 270639 Product name: LOCTITE SI 5015 BL known as Loctite(R) Superflex(R) Blue R Page 2 of 5

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Safety

showers and eye wash stations should be available.

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin

contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:PasteColor:BlueOdor:Acetic acidOdor threshold:Not available.pH:Not available.

Vapor pressure: < 10 mm hg (68 °F (20°C))

Boiling point/range: Not available. Melting point/ range: Not available. Specific gravity: 1.04 at 20 °C (68°F) Vapor density: Heavier than air. Flash point: > 93 °C (> 199.4 °F) Flammable/Explosive limits - lower: 4 % (acetic acid) Flammable/Explosive limits - upper: 19.9 % (acetic acid) Autoignition temperature: Not available. Flammability: Not applicable **Evaporation rate:** Not available.

Solubility in water: Polymerises in presence of water.

Partition coefficient (n-octanol/water):

VOC content:

Viscosity:

Decomposition temperature:

Not available.

Not available.

Not available.

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: Will not occur.

Hazardous decomposition

products:

IDH number: 270639

Acetic acid is liberated slowly upon contact with moisture. Formaldehyde.

Incompatible materials: Oxidizing agents. Bases. Water. Acids.

Reactivity: Not available.

Conditions to avoid: Prolonged heating at temperatures above 150 °C. Exposure to moisture.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation: When heated to temperatures exceeding 300° F (150° C) in the presence of air, silicones may

form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate the eyes, nose and throat. Safe handling conditions may be maintained by keeping formaldehyde vapor concentrations below the OSHA permissible

limit. Acetic acid produced during cure may irritate eyes, nose and throat.

Skin contact: Causes skin irritation.

Eye contact: Causes serious eye irritation.

Ingestion: May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Silicon dioxide	Oral LD50 (Rat) = > 22,500 mg/kg Oral LD50 (Mouse) = > 15,000 mg/kg	Nuisance dust
29H,31H-phthalocyaninato(2-)- N29,N30,N31,N32 copper	None	No Target Organs
Methylsilanetriyl triacetate	None	Irritant, Allergen
Triacetoxyethylsilane	None	No Target Organs
Gamma-glycidoxypropyl trimethoxysilane	None	Allergen, Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Silicon dioxide	No	No	No
29H,31H-phthalocyaninato(2-)- N29,N30,N31,N32 copper	No	No	No
Methylsilanetriyl triacetate	No	No	No
Triacetoxyethylsilane	No	No	No
Gamma-glycidoxypropyl trimethoxysilane	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal. Cured

rubber can be incinerated or landfilled following EPA and local regulations.

Hazardous waste number:Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None

International Air Transportation (ICAO/IATA)

Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None

Water Transportation (IMO/IMDG)

IDH number: 270639

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.

CERCLA/SARA Section 311/312: Immediate Health

CERCLA/SARA Section 313: None above reporting de minimis.

California Proposition 65: This product contains a chemical known to the State of California to cause birth defects or

other reproductive harm.

Canada Regulatory Information

IDH number: 270639

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 9

Prepared by: Product Safety and Regulatory Affairs

Issue date: 06/25/2020

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.