



Reference / Product name: Clear-Cut Flap Version/Revision (date): 7/18/2016

Printing date: 7/18/2016

page 1 of 6

Voluntary product information based on the format of a safety data sheet for coated abrasives

1. Identification of the product and of the company/undertaking

1.1 Product identifier

4-1/2x7/8 40G Clear-Cut Flap Disc PN 46640

4-1/2x7/8 60G Clear-Cut Flap Disc PN 46660

4-1/2x7/8 80G Clear-Cut Flap Disc PN 46680

1.2 Use of the product

Coated abrasives for the grinding/sanding of different kinds of materials.

1.3 Details of the supplier of the voluntary product information:

Company: IBS, Inc.

Address: 740 Clay St. NW,

Auburn, WA 98001

Phone: 800-678-1906 Fax: 800-688-3196

Website: www.industrialbolt.com

1.4 Emergency telephone number:

Chemtel Phone: 800-255-3924

2. Hazards identification

2.1. Classification

Not applicable; Abrasives are articles and not dangerous substances or mixtures according to Regulation (EC) N° 1272/2008.

See also section 8 and 16.

2.2. Label elements

Abrasives are articles and not dangerous substances or mixtures and therefore no labelling is required according to Regulation (EC) N° 1272/2008.

2.3. Other hazards

Not known.



Reference / Product name: Clear-Cut Flap Version/Revision (date): 7/18/2016

Printing date: 7/18/2016

page 2 of 6

3. Composition/information on ingredients

The product contains the following ingredients which are classified according to Regulation (EC) Nr. 1272/2008 or for which a community occupational exposure limit value exists:

Substance	EC-N°	CAS-N°	REACH Registration N°	Conc. (%)	Classification acc. to Regulation (EC) N° 1272/2008 (CLP)	
					Hazard classes/ hazard categories	Hazard statements
Cryolite(sodium- aluminium- fluoride)	237-410-6	13775-53-6	01-2119511565- 43-xxxx	1-5	Akut Tox.4	H332
					STOT RE. 1	H372
					Acut Tox. 4	H302
					Aqu.chron. 2	H411
Potassium- fluoro- borate	237-928-2	14075-53-7	01-2119968922- 24-xxxx	3-35	Skin Corr. 1B	H314
					Eye Dam. 1	H318

(For full text of H-phrases see section 16)

4. First aid measures

See also section 8 and 16

4.1. Description of first aid measures

Inhalation: Not possible, due to the form of the product

Eye contact: Not possible, due to the form of the product

Skin contact: No harmful effects known

Ingestion: Not likely, due to the form of the product; if necessary contact physician

Note to physician: Not available.

4.2. Most important symptoms and effects, both acute and delayed

Not known.

4.3. Indication of any immediate medical attention and special treatment needed

Not relevant. Treat symptomatically.

5. Fire fighting measures

5.1. Extinguishing media

Extinguishing media: water, foam, sand, powder or CO₂ as appropriate for surrounding materials





Reference / Product name: Clear-Cut Flap Version/Revision (date): 7/18/2016

Printing date: 7/18/2016

page 3 of 6

5.2. Special hazards arising from the product

Toxic fumes may occur. Use respiratory protective equipment.

5.3. Advice for fire fighters

Extinguishing materials should be selected according to the surrounding area.

6. Accidental release measures

Not applicable.

7. Handling and storage

Follow instructions of grinding machine manufacturers and the relevant national regulations. In addition, observe the safety recommendations of the manufacturer.

Store abrasives in dry, frost-free conditions avoiding wide variations in temperature. Ensure they are properly protected and supported to prevent damage and distortion.

Coated abrasives should be stored at 18-22°C, 45-65 % relative humidity.

8. Exposure controls/personal protection

8.1. Control parameters

Before grinding it is recommended to perform a risk assessment and to use personal protection equipment accordingly.

Occupational exposure limit values and/or biological limit values

Keep exposure to the following components under surveillance. (Observe also the regional official regulations)

Limit value type	substance	EC-N°	CAS-N°	Occupational limit value		Peak limit	source, remark		
(country of				Long term		Short term			
origin)				mg/	ml/m³	mg/m³	ml/m³		
				m³	(ppm)		(ppm)		
OSHA (USA)	cryolite	237-410-6	13775-53-6	1 E				4x	TRSG 900 (D)
									Fluoride
									(Fluor);
									DFG, Ŷ, H
OSHA (USA)	Potassium	237928-2	14075-53-7	2.5*					HSC,
	fluoroborate								(flourides,
									inorganic as F

Note: Hazardous dust of the workpiece material may be generated during grinding and/or sanding operations. National regulations for dust exposure limit values have to be taken into consideration.

8.2. Exposure controls

8.2.1. Individual protection measures





Reference / Product name: Clear-Cut Flap Version/Revision (date): 7/18/2016

Printing date: 7/18/2016

page 4 of 6

FEDERATION EUROPEENNE DES FABRICANTS DE PRODUITS ABRASIFS

8.2.1.1. Respiratory protection: Use respiratory protective equipment (type depends on specific application and material being ground)

8.2.1.2. Hand protection: Wear protective gloves

(type depends on specific application and material being ground)

8.2.1.3. Eye protection: Wear protective goggles or face shield (type depends on specific application and material being ground)

8.2.1.4. Hearing protection: Use hearing protection

(type depends on specific application and material being ground)

8.2.1.5. Body protection: Use protective clothing

(type depends on specific application and material being ground)

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

a) Physical state: solidb) Colour: divers

c) Solubility in water: not relevant

9.2. Other information

None.

10. Stability and reactivity

10.1. Reactivity

Coated Abrasives are stable when handled or stored correctly.

10.2. Chemical stability

No decomposition in normal use.

10.3. Possibility of hazardous reactions

No dangerous reactions known.

10.4. Conditions to avoid

Coated Abrasives are stable when handled or stored correctly.

10.5. Incompatible materials

No dangerous reactions known.

10.6. Hazardous decomposition products

At temperatures exceeding 250° C hazardous or toxic decomposition products may be generated.





Reference / Product name: Clear-Cut Flap Version/Revision (date): 7/18/2016

Printing date: 7/18/2016

page 5 of 6

11. Toxicological information

11.1. Information on toxicological effects

No toxicological effects if inhaled or swallowed or with eye or skin contact are known. See also section 8.

12. Ecological information

12.1. Toxicity

No effects known.

12.2. Persistence and degradability

No biodegradable potentials known.

12.3. Bioaccumulative potential

No potentials known.

12.4. Mobility in soil

No potentials known.

12.5. Results of PBT and vPvB assessment

Not relevant.

12.6. Other adverse effects

No effects known.

13. Disposal considerations

13.1. Waste treatment methods

13.1. Product

Follow national and regional regulations.

Due to the ingredients and properties disposal as hazardous waste (2000/532/EC) (EWC - Nr. 120120)

13.2. Packing

Follow national and regional regulations.

14. Transport information

The product is not covered by international regulation on the transport of dangerous goods.

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the product No specific labelling requirements under respective EC directives.

15.2. Chemical safety assessment

Not relevant.





Reference / Product name: Clear-Cut Flap Version/Revision (date): 7/18/2016

Printing date: 7/18/2016

page 6 of 6

16. Other information

Changes to the previous versions

See sections 1 to 16.

Literature and data sources

REACH Regulation (EC) Nr. 1907/2006
Regulation (EC) N° 1272/2008
Directive 98/24/EC
Directive 2000/39/EC
Directive 75/324/EEC
Decision 2000/532/EC
Transport regulations according to ADR, RID und IATA.

Hazard statements referred to in section 2 and 3

According to Regulation (EC) N° 1272/2008:

H332	Harmful if inhaled.
H372	Causes damage to organs through prolonged or repeated.
H302	Harmful if swallowed.
H411	Toxic to aquatic life with long lasting effects.
H319	Causes serious eye irritation.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eve damage.

The above information is based on our current standard of knowledge and does not constitute any warranty of conditions of the product. The information does not form part of any contractual agreement. It remains the user's responsibility to adhere existing laws and regulations.

Issued by: R&D