

LA-CO Industries, Inc.

# Quik Stik® TWIST PAINT MARKER White, Fluorescent Yellow, Fluorescent Green

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR  
Date of issue: 02/05/2015 Revision date: 07/21/2016 Supersedes: 02/12/2016 Version: 3.0

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Trade name : Quik Stik® TWIST PAINT MARKER White, Fluorescent Yellow, Fluorescent Green

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Marking  
Restrictions on use : No additional information available

#### 1.3. Details of the supplier of the safety data sheet

LA-CO Industries, Inc.  
1201 Pratt Boulevard  
Elk Grove Village, IL. 60007-5746  
Phone: (847) 956-7600  
Fax: (847) 956-9885  
E-mail: [customer\\_service@laco.com](mailto:customer_service@laco.com)

#### 1.4. Emergency telephone number

Emergency number : 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Skin corrosion/irritation, Category 2 H315  
Serious eye damage/eye irritation, Category 2A H319  
Reproductive toxicity, Category 2 H361  
Full text of H statements : see section 16

#### 2.2. Label elements

##### GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) : Warning

Hazard statements (GHS-US) : H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H361 - Suspected of damaging fertility or the unborn child

Precautionary statements (GHS-US) : P201 - Obtain special instructions before use  
P202 - Do not handle until all safety precautions have been read and understood  
P264 - Wash hands thoroughly after handling  
P280 - Wear eye protection, protective gloves, protective clothing  
P302+P352 - If on skin: Wash with plenty of water  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P308+P313 - If exposed or concerned: Get medical advice/attention  
P321 - Specific treatment (see First aid measures on this label)  
P332+P313 - If skin irritation occurs: Get medical advice/attention  
P337+P313 - If eye irritation persists: Get medical advice/attention  
P362+P364 - Take off contaminated clothing and wash it before reuse  
P405 - Store locked up  
P501 - Dispose of contents/container to Dispose in a safe manner in accordance with local/national regulations

#### 2.3. Other hazards

No additional information available

# Quik Stik® TWIST PAINT MARKER White, Fluorescent Yellow, Fluorescent Green

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

### 2.4. Unknown acute toxicity (GHS US)

31.42% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)

31.42% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

31.42% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
1-butoxypropan-2-ol	(CAS No) 5131-66-8	30.4 – 31.04 White 34.19 – 34.91 Fluorescent Green 35.11 – 35.85 Fluorescent Yellow	Flam. Liq. 4, H227 Skin Irrit. 2, H315 Eye Irrit. 2A, H319
(2-Methoxymethylethoxy)-propanol	(CAS No) 34590-94-8	8 White < 9.42 Fluorescent Green < 9.68 Fluorescent Yellow	Flam. Liq. 4, H227
N-Ethyl O/P Toluene Sulfonamides	(CAS No) 8047-99-2	4 White 1.45 Fluorescent Green 1.5 Fluorescent Yellow	Acute Tox. 3 (Dermal), H311
4-tert-butylphenol	(CAS No) 98-54-4	0.4 – 0.16 White 0.15 – 0.77 Fluorescent Green 0.16 – 0.4 Fluorescent Yellow	Skin Irrit. 2, H315 Eye Dam. 1, H318 Repr. 2, H361 STOT SE 3, H335 Aquatic Chronic 2, H411

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
First-aid measures after skin contact	: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Get medical advice/attention if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: Suspected of damaging fertility or the unborn child.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

All treatments should be based on observed signs and symptoms of distress in the patient.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: None known.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Combustible. Combustion generates : Carbon oxides (CO, CO <sub>2</sub> ). Nitrogen oxides. Sulphur oxides. metallic oxides.
Explosion hazard	: Product is not explosive.
Reactivity	: No dangerous reactions known.

### 5.3. Advice for firefighters

Firefighting instructions	: Exercise caution when fighting any chemical fire. Do not allow run-off from fire fighting to enter drains or water courses.
---------------------------	---

# Quik Stik® TWIST PAINT MARKER White, Fluorescent Yellow, Fluorescent Green

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Wear a self contained breathing apparatus. Wear fire/flame resistant/retardant clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid contact with skin and eyes. Avoid creating or spreading dust.

##### 6.1.1. For non-emergency personnel

Protective equipment : Chemical goggles or safety glasses. Wear suitable protective clothing and gloves.

Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

Protective equipment : Chemical goggles or safety glasses. Wear suitable protective clothing and gloves.

Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment : Contain and collect as any solid.

Methods for cleaning up : Sweep spilled substance into containers; if appropriate, moisten first to prevent dusting.

#### 6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Hygiene measures : Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep away from ignition sources. Keep container closed when not in use. Protect from sunlight.

Incompatible products : Strong oxidizers. Acids.

Incompatible materials : Sources of ignition.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Quik Stik® TWIST PAINT MARKER White, Fluorescent Yellow, Fluorescent Green		
ACGIH	Not applicable	
OSHA	Not applicable	
N-Ethyl O/P Toluene Sulfonamides (8047-99-2)		
ACGIH	Not applicable	
OSHA	Not applicable	
4-tert-butylphenol (98-54-4)		
ACGIH	Not applicable	
OSHA	Not applicable	
1-butoxypropan-2-ol (5131-66-8)		
ACGIH	Not applicable	
OSHA	Not applicable	
(2-Methoxymethylethoxy)-propanol (34590-94-8)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	606 mg/m <sup>3</sup>
ACGIH	ACGIH TWA (ppm)	100 ppm

# Quik Stik® TWIST PAINT MARKER White, Fluorescent Yellow, Fluorescent Green

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

### (2-Methoxymethylethoxy)-propanol (34590-94-8)

ACGIH	ACGIH STEL (mg/m <sup>3</sup> )	909 mg/m <sup>3</sup>
ACGIH	ACGIH STEL (ppm)	150 ppm
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
OSHA	OSHA PEL (STEL) (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
Canada (Quebec)	VECD (mg/m <sup>3</sup> )	909 mg/m <sup>3</sup>
Canada (Quebec)	VECD (ppm)	150 ppm
Canada (Quebec)	VEMP (mg/m <sup>3</sup> )	606 mg/m <sup>3</sup>
Canada (Quebec)	VEMP (ppm)	100 ppm

### 8.2. Exposure controls

Appropriate engineering controls	: Either local exhaust or general room ventilation is usually required.
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Wear suitable gloves. Use rubber gloves.
Eye protection	: Chemical goggles or safety glasses.
Skin and body protection	: Wear suitable protective clothing. Long sleeved protective clothing.
Respiratory protection	: Where excessive vapour may result, wear approved mask. Use air-purifying respirator equipped with particulate filtering cartridges.
Other information	: Do not eat, drink or smoke when using this product.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: A solid crayon-like marker.
Colour	: Variable
Odour	: Solvent
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 62 °C
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

### 9.2. Other information

VOC content	: 48.87 %
-------------	-----------

# Quik Stik® TWIST PAINT MARKER White, Fluorescent Yellow, Fluorescent Green

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No dangerous reactions known.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

Heat. Direct sunlight.

#### 10.5. Incompatible materials

Strong acids. Strong oxidizers.

#### 10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide. Nitrogen oxides. metallic oxides. Sulphur oxides.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

**Likely routes of exposure** : Skin and eye contact

**Acute toxicity** : Not classified

<b>N-Ethyl O/P Toluene Sulfonamides (8047-99-2)</b>	
LD50 oral rat	2250 mg/kg
LD50 dermal rabbit	1000 mg/kg
ATE US (oral)	2250.000 mg/kg bodyweight
ATE US (dermal)	1000.000 mg/kg bodyweight
<b>4-tert-butylphenol (98-54-4)</b>	
LD50 oral rat	> 2000 mg/kg No mortality observed
LD50 dermal rabbit	> 16 g/kg No mortality observed
LC50 inhalation rat (mg/l)	5.6 mg/l/4h
ATE US (vapours)	5.600 mg/l/4h
ATE US (dust,mist)	5.600 mg/l/4h
<b>1-butoxypropan-2-ol (5131-66-8)</b>	
LD50 oral rat	3300 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 inhalation rat (ppm)	> 651 ppm/4h
ATE US (oral)	3300.000 mg/kg bodyweight
<b>(2-Methoxymethylethoxy)-propanol (34590-94-8)</b>	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 19020 mg/kg
LC50 inhalation rat (mg/l)	> 1667 mg/l/4h

**Skin corrosion/irritation** : Causes skin irritation.

**Serious eye damage/irritation** : Causes serious eye irritation.

**Respiratory or skin sensitisation** : Not classified

**Germ cell mutagenicity** : Not classified

**Carcinogenicity** : Not classified.

**Reproductive toxicity** : Suspected of damaging fertility or the unborn child.

**Specific target organ toxicity (single exposure)** : Not classified

**Specific target organ toxicity (repeated exposure)** : Not classified

**Aspiration hazard** : Not classified

Symptoms/injuries after skin contact : Causes skin irritation.

# Quik Stik® TWIST PAINT MARKER White, Fluorescent Yellow, Fluorescent Green

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

Symptoms/injuries after eye contact : Causes serious eye irritation.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : No additional information available.

4-tert-butylphenol (98-54-4)	
LC50 fish 1	> 1 mg/l 96 h
EC50 Daphnia 1	4.8 mg/l 48 h
1-butoxypropan-2-ol (5131-66-8)	
LC50 fish 1	> 560 (560 - 1000) mg/l 96 h
EC50 Daphnia 1	> 1000 mg/l 48 h
(2-Methoxymethylethoxy)-propanol (34590-94-8)	
LC50 fish 1	> 1000 mg/l <i>Poecilia reticulata</i>
ErC50 (algae)	> 1000 mg/l

#### 12.2. Persistence and degradability

Quik Stik® TWIST PAINT MARKER White, Fluorescent Yellow, Fluorescent Green	
Persistence and degradability	Not established.
4-tert-butylphenol (98-54-4)	
Biodegradation	60 % 28 d
1-butoxypropan-2-ol (5131-66-8)	
Persistence and degradability	Readily biodegradable.
(2-Methoxymethylethoxy)-propanol (34590-94-8)	
Persistence and degradability	Readily biodegradable.

#### 12.3. Bioaccumulative potential

Quik Stik® TWIST PAINT MARKER White, Fluorescent Yellow, Fluorescent Green	
Bioaccumulative potential	Not established.
4-tert-butylphenol (98-54-4)	
Log Pow	3
1-butoxypropan-2-ol (5131-66-8)	
Log Pow	1.2

#### 12.4. Mobility in soil

Quik Stik® TWIST PAINT MARKER White, Fluorescent Yellow, Fluorescent Green	
Ecology - soil	No additional information available.

#### 12.5. Other adverse effects

Other information : No additional information available.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Sewage disposal recommendations : Do not dispose of waste into sewer.  
Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

### SECTION 14: Transport information

In accordance with US-DOT 49-CFR and the HMR / TDG / ADR / IMDG / ICAO / IATA

In accordance with DOT  
Not regulated.

#### TDG

Not regulated.

# Quik Stik® TWIST PAINT MARKER White, Fluorescent Yellow, Fluorescent Green

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

### Transport by sea

Not regulated.

### Air transport

Not regulated.

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

#### (2-Methoxymethylethoxy)-propanol (34590-94-8)

EPA TSCA Regulatory Flag

T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA

### 15.2. International regulations

#### National regulations

**Quik Stik® TWIST PAINT MARKER White, Fluorescent Yellow, Fluorescent Green**

All components are listed on the EEC inventory European Inventory of Existing Commercial Chemical Substances (EINECS)  
All ingredients are listed on the Canadian Domestic Substances List (DSL) or Non-Domestic Substances List (NDSL)

### 15.3. US State regulations

**Quik Stik® TWIST PAINT MARKER White, Fluorescent Yellow, Fluorescent Green**

State or local regulations

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer, developmental and/or reproductive harm

#### (2-Methoxymethylethoxy)-propanol (34590-94-8)

U.S. - Idaho - Occupational Exposure Limits - Ceilings  
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations  
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - New York - Right to Know List of Hazardous Chemicals  
U.S. - Minnesota - Hazardous Substance List  
U.S. - Washington - Permissible Exposure Limits - TWAs  
U.S. - Washington - Permissible Exposure Limits - STELs  
U.S. - Massachusetts - Right To Know List  
U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16: Other information

Revision date

: 07/21/2016

Data sources

: Canadian Centre for Occupational Health and Safety. Accessed at:

[http://www.ccohs.ca/oshanswers/legisl/whmis\\_classifi.html](http://www.ccohs.ca/oshanswers/legisl/whmis_classifi.html).

ESIS (European chemical Substances Information System; accessed at:

<http://esis.jrc.ec.europa.eu/index.php?PGM=cla>.

European Chemicals Agency (ECHA) Registered Substances list. Accessed at <http://echa.europa.eu/>. Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition.

National Fire Protection Association; Fire Protection Guide to Hazardous Materials; 10th edition.

OSHA 29CFR 1910.1200 Hazard Communication Standard.

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

TSCA Chemical Substance Inventory. Accessed at

<http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.

# Quik Stik® TWIST PAINT MARKER White, Fluorescent Yellow, Fluorescent Green

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

Other information : None.

Full text of H-statements:

H227	Combustible liquid
H311	Toxic in contact with skin
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H361	Suspected of damaging fertility or the unborn child
H411	Toxic to aquatic life with long lasting effects

Abbreviations and acronyms:

	ACGIH (American Conference of Government Industrial Hygienists)
	ATE: Acute Toxicity Estimate
	CAS (Chemical Abstracts Service) number
	CLP: Classification, Labelling, Packaging.
	EC50: Environmental Concentration associated with a response by 50% of the test population.
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
	LD50: Lethal Dose for 50% of the test population
	PBT: Persistent, Bioaccumulative, Toxic
	TSCA: Toxic Substances Control Act

NFPA health hazard


: 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA fire hazard

: 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and not reactive with water.



Indication of changes:

Added. Product.

**SDS Prepared by:** The Redstone Group, LLC  
6077 Frantz Rd.  
Suite 206  
Dublin, OH USA 43016  
T 614-923-7472  
[www.redstonegrp.com](http://www.redstonegrp.com)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*