

Safety Data Sheet

Printing date 04/16/2015

Revised On 04/16/2015

1 Identification of the substance and manufacturer

Trade name: NEW CEILING WHITE
Product code: 0000200051
IBS Part Number: 81751
Product category: PC9a Paints and coatings.
Manufacturer/Supplier: Seymour of Sycamore
 917 Crosby Avenue, Sycamore, IL 60178
 Phone: 815-895-9101 www.seymourpaint.com
Emergency telephone number: CHEMTEL 1-800-255-3924, or 813-248-0585.



2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.
 Press. Gas H280 Contains gas under pressure; may explode if heated.
 Carc. 2 H351 Suspected of causing cancer.
 Repr. 2 H361 Suspected of damaging fertility or the unborn child.
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.
 Skin Irrit. 2 H315 Causes skin irritation.

GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

Signal word

Hazard statements

Danger
 Extremely flammable aerosol.
 Contains gas under pressure; may explode if heated.
 Causes skin irritation.
 Suspected of causing cancer.
 Suspected of damaging fertility or the unborn child.
 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

If medical advice is needed, have product container or label at hand.
 Keep out of reach of children.
 Read label before use.
 Obtain special instructions before use.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Do not spray on an open flame or other ignition source.
 Pressurized container: Do not pierce or burn, even after use.
 Wash hands thoroughly after handling.
 Do not handle until all safety precautions have been read and understood.
 Wear protective gloves.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 If skin irritation occurs: Get medical advice/attention.
 If on skin: Wash with plenty of water.
 Get medical advice/attention if you feel unwell.
 IF exposed or concerned: Get medical advice/attention.
 Specific treatment (see on this label).
 Take off contaminated clothing and wash it before reuse.
 Store locked up.
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 Store in a well-ventilated place.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

74-98-6	propane	18.95%
108-88-3	Toluene	13.89%
106-97-8	n-butane	11.13%
13463-67-7	titanium dioxide	9.76%
64742-89-8	VM&P Naphtha	5.98%
1317-65-3	Calcium Carbonate	5.4%
64742-47-8	Mineral Spirits	2.39%
1330-20-7	xylene (mix)	2.31%
108-65-6	PM acetate	1.47%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.
After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
After swallowing: Rinse out mouth and then drink plenty of water.
 Rinse mouth with water. Do not induce vomiting.

Most important symptoms and effects:

Dizziness

(Contd. on page 2)

Safety Data Sheet

Printing date 04/16/2015

Revised On 04/16/2015

Trade name: NEW CEILING WHITE

(Contd. of page 1)

Indication of any immediate medical attention needed:

No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: CO₂, extinguishing powder or water spray. Fight larger fires with water spray.
Special hazards: Can form explosive gas-air mixtures.
Protective equipment for firefighters: A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures: Wear protective equipment. Keep unprotected persons away. Use respiratory protective device against the effects of fumes/dust/aerosol.
Methods and material for containment and cleaning up: Ensure adequate ventilation. Dispose contaminated material as waste according to section 13.

7 Handling and storage

Precautions for safe handling: Use only in well ventilated areas.
Storage requirements: Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure controls/personal protection**Components with limit values that require monitoring at the workplace:****74-98-6 propane**

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm
REL (USA) Long-term value: 1800 mg/m³, 1000 ppm
TLV (USA) refer to Appendix F

108-88-3 Toluene

PEL (USA) Long-term value: 200 ppm
Ceiling limit value: 300; 500* ppm
*10-min peak per 8-hr shift
REL (USA) Short-term value: 560 mg/m³, 150 ppm
Long-term value: 375 mg/m³, 100 ppm
TLV (USA) Long-term value: 75 mg/m³, 20 ppm
BEI

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m³, 800 ppm
TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm

1330-20-7 xylene (mix)

PEL (USA) Long-term value: 435 mg/m³, 100 ppm
REL (USA) Short-term value: 655 mg/m³, 150 ppm
Long-term value: 435 mg/m³, 100 ppm
TLV (USA) Short-term value: 651 mg/m³, 150 ppm
Long-term value: 434 mg/m³, 100 ppm
BEI

108-65-6 PM acetate

WEEL (USA) Long-term value: 50 ppm

Ingredients with biological limit values:**108-88-3 Toluene**

BEI (USA) 0.02 mg/L
Medium: blood
Time: prior to last shift of workweek
Parameter: Toluene

0.03 mg/L
Medium: urine
Time: end of shift
Parameter: Toluene

0.3 mg/g creatinine
Medium: urine
Time: end of shift
Parameter: o-Cresol with hydrolysis (background)

1330-20-7 xylene (mix)

BEI (USA) 1.5 g/g creatinine
Medium: urine
Time: end of shift
Parameter: Methylhippuric acids

Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use.
Wash hands after use.
Do not eat or drink while working.

(Contd. on page 3)

Safety Data Sheet

Printing date 04/16/2015

Revised On 04/16/2015

Trade name: NEW CEILING WHITE

(Contd. of page 2)

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection: Protective gloves. The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Appearance: Aerosol.
Odor: Aromatic
Odor threshold: Not determined.
pH-value: Not determined.
Melting point/Melting range Undetermined.
Boiling point: -44 °C (-47 °F)
Flash point: -19 °C (-2 °F)
Flammability (solid, gas): Extremely flammable.
Decomposition temperature: Not determined.
Auto igniting: Product is not self-igniting.
Danger of explosion: In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit: 1.5 Vol %
Upper Explosion Limit: 10.9 Vol %
Vapor pressure: Not determined.
Relative Density: Between 0.77 and 0.85 (Water equals 1.00)
Vapour density Not determined.
Evaporation rate Not applicable.
Partition coefficient: n-octonal/water: Not determined.
Solubility: Not determined.
Viscosity: Not determined.
VOC content: 571.9 g/l / 4.77 lb/gl
VOC content (less exempt solvents): 56.8 %
Water: 21.3 %
MIR Value: 1.10
Solids content: 21.7 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures.
Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
Chemical stability: Not fully evaluated.
Possibility of hazardous reactions: No dangerous reactions known.
Incompatible materials: No further relevant information available.
Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:

106-97-8 n-butane

Inhalative	LC50/4 h	658 mg/l (rat)
------------	----------	----------------

13463-67-7 titanium dioxide

Oral	LD50	>20000 mg/kg (rat)
Dermal	LD50	>10000 mg/kg (rbt)
Inhalative	LC50/4 h	>6.82 mg/l (rat)

1330-20-7 xylene (mix)

Oral	LD50	8700 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rbt)
Inhalative	LC50/4 h	6350 mg/l (rat)

108-65-6 PM acetate

Oral	LD50	8500 mg/kg (rat)
Inhalative	LC50/4 h	35.7 mg/l (rat)

Information on toxicological effects: No data available.
Skin effects: No irritant effect.
Eye effects: No irritating effect.
Sensitization: No sensitizing effects known.

Carcinogenic categories

IARC (International Agency for Research on Cancer)

108-88-3	Toluene	3
13463-67-7	titanium dioxide	2B
1330-20-7	xylene (mix)	3

(Contd. on page 4)

Safety Data Sheet

Printing date 04/16/2015

Revised On 04/16/2015

Trade name: NEW CEILING WHITE

(Contd. of page 3)

NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.
Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.
Bioaccumulative potential: No further relevant information available.
Mobility in soil: No further relevant information available.
Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.
Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number UN1950
DOT N/A
DOT UN1950
DOT Consumer Commodity ORM-D
ADR Aerosols, flammable
Transport hazard class(es): 1950 Aerosols
Class 2.1
Marine pollutant: No
Special precautions for user: Warning: Gases
EMS Number: F-D,S-U
Packaging Group: --
UN "Model Regulation": UN1950, Aerosols, 2.1

15 Regulatory information**SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-88-3	Toluene
1330-20-7	xylene (mix)

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.**California Proposition 65 chemicals known to cause cancer:**

13463-67-7	titanium dioxide
100-41-4	ethyl benzene

California Proposition 65 chemicals known to cause developmental toxicity:

108-88-3 Toluene

CANADIAN ENVIRONMENTAL PROTECTION ACT:

All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

EPA:

108-88-3	Toluene	II
1330-20-7	xylene (mix)	I

16 Other information

Contact: Regulatory Affairs
Date of preparation / last revision 04/16/2015 / -