

SAFETY DATA SHEET

Classified in accordance 29 CFR 1910.1200

1. Identification

Product identifier: AIR TOOL CONDITIONER

Other means of identification
DfcXi WbC" 74136

Recommended restrictions
Recommended use: Cleaner
Restrictions on use: Not known.

Distributor Information

Company Name: IBS, INC.
Address: PO BOX 1717
AUBURN, WA 98071-1717
US
Telephone: 1-800-678-1906

Emergency telephone number: 1-800-255-3924 CHEM-TEL

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable aerosol Category 1

Health Hazards

Aspiration Hazard Category 1

Environmental Hazards

Acute hazards to the aquatic environment Category 2

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Extremely flammable aerosol.
May be fatal if swallowed and enters airways.
Toxic to aquatic life.

Precautionary Statements

- Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid release to the environment.
- Response:** IF SWALLOWED: Immediately call a POISON CENTER/doctor Do NOT induce vomiting.
- Storage:** Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store locked up.
- Disposal:** Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Distillates (petroleum), light distillate hydrotreating process, low-boiling	68410-97-9	25 - <50%
Naphtha (petroleum), light alkylate	64741-66-8	10 - <25%
Butane	106-97-8	10 - <20%
White mineral oil (petroleum)	8042-47-5	10 - <20%
Petrolatum	8009-03-8	5 - <10%
Ethanol	64-17-5	5 - <10%
Propane	74-98-6	5 - <10%
Solvent naphtha (petroleum), light aliph.	64742-89-8	1 - <5%
Heptane	142-82-5	1 - <5%
Heptane, branched, cyclic and linear	426260-76-6	1 - <2.5%
Naphtha (petroleum), hydrotreated light	64742-49-0	1 - <5%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

The exact concentration has been withheld as a trade secret.

4. First-aid measures

Description of necessary first-aid measures

- Inhalation:** Move to fresh air.
- Skin Contact:** Wash skin thoroughly with soap and water. If skin irritation occurs: Get medical advice/attention.
- Eye contact:** Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.
- Ingestion:** Call a physician or poison control center immediately. Rinse mouth. Never give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Personal Protection for First-aid Responders: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Most important symptoms/effects, acute and delayed

Symptoms: No data available.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: Vapors may travel considerable distance to a source of ignition and flash back.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind.

Accidental release measures: Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk.

Methods and material for containment and cleaning up: Absorb spill with vermiculite or other inert material, then place in a container for chemical waste.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Handling

Technical measures (e.g. Local and general ventilation): No data available.

Safe handling advice: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.

Contact avoidance measures: No data available.

Storage

Safe storage conditions: Store locked up. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Aerosol Level 3

Safe packaging materials: No data available.

Storage Temperature: No data available.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Distillates (petroleum), light distillate hydrotreating process, low-boiling - Mist.	STEL	10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	TWA	5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	REL	5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Butane	REL	800 ppm 1,900 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	STEL	1,000 ppm	US. ACGIH Threshold Limit Values, as amended
	TWA	800 ppm 1,900 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	REL	5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
White mineral oil (petroleum) - Mist.	STEL	10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	REL	5 mg/m3	US. ACGIH Threshold Limit Values, as amended
White mineral oil (petroleum) - Inhalable fraction.	STEL	10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Petrolatum - Mist.	STEL	10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Petrolatum - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values, as amended
Petrolatum - Mist.	REL	5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Ethanol	REL	1,000 ppm 1,900 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended



	PEL	1,000 ppm	1,900 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	1,000 ppm	1,900 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	STEL	1,000 ppm		US. ACGIH Threshold Limit Values, as amended
Propane	REL	1,000 ppm	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Solvent naphtha (petroleum), light aliph.	TWA	100 ppm	400 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	PEL	100 ppm	400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	REL	100 ppm	400 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Naphtha (petroleum), hydrotreated light	REL	100 ppm	400 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	TWA	100 ppm	400 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	PEL	100 ppm	400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Heptane	TWA	400 ppm	1,600 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	REL	85 ppm	350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	STEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	TWA	400 ppm		US. ACGIH Threshold Limit Values, as amended
	STEL	500 ppm		US. ACGIH Threshold Limit Values, as amended
	Ceil_Time	440 ppm	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
2-Propanol, 2-methyl-	STEL	150 ppm	450 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	TWA	100 ppm	300 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	PEL	100 ppm	300 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	100 ppm		US. ACGIH Threshold Limit Values, as amended
	STEL	150 ppm	450 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	REL	100 ppm	300 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Distillates (petroleum), hydrotreated heavy naphthenic	TWA	400 ppm	1,600 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Distillates (petroleum), hydrotreated heavy naphthenic - Mist.	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	STEL		10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Distillates (petroleum), hydrotreated heavy naphthenic	Ceil_Time		1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Distillates (petroleum), hydrotreated heavy naphthenic - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values, as amended
Distillates (petroleum), hydrotreated heavy naphthenic	REL		350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Distillates (petroleum), hydrotreated heavy paraffinic <3% DMSO - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values, as amended



Distillates (petroleum), hydrotreated heavy paraffinic <3% DMSO - Mist.	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	STEL		10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Distillates, Petroleum, Hydrotreated Light Naphthenic - Mist.	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Distillates, Petroleum, Hydrotreated Light Naphthenic	TWA	400 ppm	1,600 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Distillates, Petroleum, Hydrotreated Light Naphthenic - Mist.	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	STEL		10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Distillates, Petroleum, Hydrotreated Light Naphthenic	Ceil_Time		1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	REL		350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Distillates, Petroleum, Hydrotreated Light Naphthenic - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values, as amended
Distillates (petroleum), solvent-dewaxed heavy paraffinic	TWA	400 ppm	1,600 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Distillates (petroleum), solvent-dewaxed heavy paraffinic - Mist.	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	STEL		10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Distillates (petroleum), solvent-dewaxed heavy paraffinic - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values, as amended
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Ceil_Time		1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	REL		350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Distillates (petroleum), hydrotreated light paraffinic - Mist.	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	STEL		10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Distillates (petroleum), hydrotreated light paraffinic - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values, as amended
Distillates (petroleum), solvent-dewaxed light paraffinic - Mist.	STEL		10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended



	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Distillates (petroleum), solvent-dewaxed light paraffinic - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values, as amended
Benzene, methyl-	STEL	150 ppm	560 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	REL	100 ppm	375 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	TWA	100 ppm	375 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	Ceiling	300 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000), as amended
	TWA	20 ppm		US. ACGIH Threshold Limit Values, as amended
	TWA	200 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000), as amended
	MAX. CONC	500 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000), as amended
	STEL	150 ppm	560 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Benzene	REL	0.1 ppm		US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	TWA	1 ppm		US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	Ceiling	25 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000), as amended
	TWA	0.5 ppm		US. ACGIH Threshold Limit Values, as amended
	STEL	2.5 ppm		US. ACGIH Threshold Limit Values, as amended
	STEL	5 ppm		US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended
	OSHA_ACT	0.5 ppm		US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended
	TWA	10 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000), as amended
	MAX. CONC	50 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000), as amended
	STEL	5 ppm		US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	TWA	1 ppm		US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended
	STEL	1 ppm		US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Benzene, (1-methylethyl)-	REL	50 ppm	245 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	TWA	50 ppm		US. ACGIH Threshold Limit Values, as amended
	PEL	50 ppm	245 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	50 ppm	245 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	TWA	1 ppm		US. ACGIH Notice of Intended Changes (NIC) to Threshold Limit Values, as amended
Benzene, ethyl-	STEL	125 ppm	545 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	STEL	125 ppm	545 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	TWA	100 ppm	435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	TWA	20 ppm		US. ACGIH Threshold Limit Values, as amended

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Benzene, methyl- (toluene: Sampling time: End of shift.)	0.03 mg/l (Urine)	ACGIH BEL
Benzene, methyl- (o-Cresol, with hydrolysis: Sampling time: End of shift.)	0.3 mg/g (Creatinine in urine)	ACGIH BEL
Benzene, methyl- (toluene: Sampling time: Prior to last shift of work week.)	0.02 mg/l (Blood)	ACGIH BEL
Benzene (S-Phenylmercapturic acid: Sampling time: End of shift.)	25 µg/g (Creatinine in urine)	ACGIH BEL

Benzene (t,t-Muconic acid: Sampling time: End of shift.)	500 µg/g (Creatinine in urine)	ACGIH BEL
Benzene, ethyl- (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL

Exposure guidelines

Benzene	US. ACGIH Threshold Limit Values, as amended	Can be absorbed through the skin.
---------	--	-----------------------------------

Appropriate Engineering Controls No data available.

Individual protection measures, such as personal protective equipment

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: No data available.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.

Hygiene measures: Observe good industrial hygiene practices. When using do not smoke.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	Spray Aerosol
Color:	No data available.
Odor:	No data available.
Odor Threshold:	No data available.
pH:	No data available.
Freezing point:	No data available.
Boiling Point:	Estimated 95 °C
Flash Point:	Estimated -104.4 °C
Evaporation Rate:	No data available.
Flammability (solid, gas):	No data available.
Explosive limit - upper (%):	Estimated 9.5 %(V)
Explosive limit - lower (%):	Estimated 1.9 %(V)
Vapor pressure:	2,068 - 3,447 hPa (20 °C)
Vapor density (air=1):	No data available.
Density:	No data available.
Relative density:	No data available.
Solubility in Water:	No data available.
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Self Ignition Temperature:	No data available.
Decomposition Temperature:	No data available.
Kinematic viscosity:	No data available.
Dynamic viscosity:	No data available.
Explosive properties:	No data available.
Oxidizing properties:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	No data available.
Hazardous Decomposition Products:	No data available.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: Not classified for acute toxicity based on available data.

Dermal

Product: Not classified for acute toxicity based on available data.

Inhalation

Product: Not classified for acute toxicity based on available data.

Repeated dose toxicity

Product: No data available.

Components:

Distillates (petroleum), light distillate	NOAEL (Rat(Female, Male), Inhalation): 9,840 mg/m ³ Inhalation Experimental result, Key study
hydrotreating process, low-boiling	NOAEL (Rat(Female, Male), Dermal, 5 - 28 d): 3,750 mg/kg Dermal Experimental result, Key study
	NOAEL (Rat(Male), Oral, 28 d): < 500 mg/kg Oral Experimental result, Supporting study

Naphtha (petroleum), light alkylate	NOAEL (Mouse, Rat(Female, Male), Inhalation, 107 - 113 Weeks): 1,402 mg/m ³ Inhalation Experimental result, Key study NOAEL (Rat(Female, Male), Dermal, 5 - 28 d): 3,750 mg/kg Dermal Experimental result, Key study
Butane	LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation Experimental result, Key study NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Experimental result, Key study
White mineral oil (petroleum) Petrolatum	NOAEL (Rat(Female, Male), Oral, 90 d): >= 20,000 ppm(m) Oral Experimental result, Key study NOAEL (Rat(Female, Male), Dermal, 13 Weeks): > 2,000 mg/kg Dermal Read-across from supporting substance (structural analogue or surrogate), Key study
Ethanol	NOAEL (Rat(Male), Oral, 7 - 14 Weeks): 10 %(m) Oral Experimental result, Key study
Propane	NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Experimental result, Key study LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation Experimental result, Key study
Solvent naphtha (petroleum), light aliph.	NOAEL (Mouse, Rat(Female, Male), Inhalation, 107 - 113 Weeks): 1,402 mg/m ³ Inhalation Experimental result, Key study NOAEL (Rat(Female, Male), Dermal, 5 - 28 d): 3,750 mg/kg Dermal Experimental result, Key study NOAEL (Rat(Female, Male), Dermal, 28 d): > 375 mg/kg Dermal Experimental result, Supporting study
Heptane	NOAEL (Rat(Male), Inhalation): 12,470 mg/m ³ Inhalation Experimental result, Key study
Naphtha (petroleum), hydrotreated light	NOAEL (Rat(Female, Male), Inhalation): 10,000 mg/m ³ Inhalation Experimental result, Key study LOAEL (Rat(Female, Male), Oral, 13 Weeks): 1,250 mg/kg Oral Read-across based on grouping of substances (category approach), Key study NOAEL (Rat(Female, Male), Dermal, 28 d): > 375 mg/kg Dermal Experimental result, Supporting study

Skin Corrosion/Irritation

Product: No data available.

Components:

Distillates (petroleum), light distillate hydrotreating process, low-boiling	Assessment Not irritating
Naphtha (petroleum), light alkylate	In vitro (Human): not corrosive
White mineral oil (petroleum)	in vivo (Rabbit): Not irritant
Petrolatum	in vivo (Rabbit): Not irritant
Ethanol	in vivo (Rabbit): Not irritant
Solvent naphtha (petroleum), light aliph.	Assessment Non-Irritating
Heptane	in vivo (Rabbit): Irritating
Heptane, branched, cyclic and linear	Assessment Irritating.
Naphtha (petroleum), hydrotreated light	Assessment Non-Irritating In vitro (Human): not corrosive

Serious Eye Damage/Eye Irritation

Product: No data available.



Components:

Distillates (petroleum), light distillate hydrotreating process, low-boiling	Rabbit, 24 - 72 hrs: Not irritating
Naphtha (petroleum), light alkylate	Rabbit, 24 - 72 hrs: Not irritating
White mineral oil (petroleum)	Rabbit, 24 - 72 hrs: Not irritating
Petrolatum	Rabbit, 24 - 72 hrs: Not irritating
Ethanol	Rabbit, 1 - 24 hrs: Not irritating
Solvent naphtha (petroleum), light aliph.	Rabbit: Not irritating
Heptane	Rabbit, 24 - 72 hrs: Not irritating
Naphtha (petroleum), hydrotreated light	Rabbit, 24 - 72 hrs: Not irritating

Respiratory or Skin Sensitization

Product: No data available.

Components:

Distillates (petroleum), light distillate hydrotreating process, low-boiling	Skin sensitization:, in vivo (Guinea pig): Non sensitising
Naphtha (petroleum), light alkylate	Skin sensitization:, in vivo (Guinea pig): Non sensitising
White mineral oil (petroleum)	Skin sensitization:, in vivo (Guinea pig): Non sensitising
Petrolatum	Skin sensitization:, in vivo (Guinea pig): Non sensitising
Ethanol	Skin sensitization:, in vivo (Guinea pig): Non sensitising
Solvent naphtha (petroleum), light aliph.	Skin sensitization:, in vivo (Guinea pig): Non sensitising
Heptane	Skin sensitization:, in vivo (Guinea pig): Non sensitising
Naphtha (petroleum), hydrotreated light	Skin sensitization:, in vivo (Guinea pig): Non sensitising

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo
Product: No data available.

Reproductive toxicity
Product: No data available.

Specific Target Organ Toxicity - Single Exposure
Product: No data available.

Components:
Heptane Narcotic effect. - Category 3 with narcotic effects.

Specific Target Organ Toxicity - Repeated Exposure
Product: No data available.

Aspiration Hazard
Product: No data available.

Components:

Distillates (petroleum), light distillate hydrotreating process, low-boiling	May be fatal if swallowed and enters airways.
Naphtha (petroleum), light alkylate	May be fatal if swallowed and enters airways.
White mineral oil (petroleum)	May be fatal if swallowed and enters airways.
Solvent naphtha (petroleum), light aliph.	May be fatal if swallowed and enters airways.
Heptane	May be fatal if swallowed and enters airways.
Heptane, branched, cyclic and linear	May be fatal if swallowed and enters airways.
Naphtha (petroleum), hydrotreated light	May be fatal if swallowed and enters airways.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:	No data available.
Components:	
Distillates (petroleum), light distillate hydrotreating process, low-boiling	LL 50 (Pimephales promelas, 96 h): 8.2 mg/l Experimental result, Key study
Naphtha (petroleum), light alkylate	LL 50 (Oncorhynchus mykiss, 96 h): 10 mg/l Experimental result, Key study
Butane	LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study
White mineral oil (petroleum)	NOAEL (Oncorhynchus mykiss, 96 h): >= 100 mg/l Experimental result, Key study

Petrolatum	NOAEL (Pimephales promelas, 96 h): ≥ 100 mg/l Read-across from supporting substance (structural analogue or surrogate), Key study
Ethanol	LC 50 (Pimephales promelas, 96 h): 15.3 g/l Experimental result, Key study
Propane	LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study
Heptane	LC 50 (Mozambique tilapia (Tilapia mossambica), 96 h): 375 mg/l Mortality
Naphtha (petroleum), hydrotreated light	LC 50 (96 h): 8.41 mg/l Experimental result, Key study

Aquatic Invertebrates

Product: No data available.

Components:

Distillates (petroleum), light distillate hydrotreating process, low-boiling	EC 50 (Daphnia magna, 48 h): 4.5 mg/l Experimental result, Key study NOAEL (Daphnia magna, 48 h): 0.5 mg/l Experimental result, Key study
Naphtha (petroleum), light alkylate	EC 50 (Daphnia magna, 48 h): 4.5 mg/l Experimental result, Key study
Butane	LC 50 (Daphnia sp., 48 h): 69.43 mg/l QSAR QSAR, Key study
White mineral oil (petroleum)	NOAEL (Daphnia magna, 48 h): ≥ 100 mg/l Experimental result, Key study
Petrolatum	EC 50 (Daphnia magna, 48 h): $> 10,000$ mg/l Read-across from supporting substance (structural analogue or surrogate), Key study
Ethanol	LC 50 (Ceriodaphnia dubia, 48 h): 5,012 mg/l Experimental result, Key study
Solvent naphtha (petroleum), light aliph.	EC 50 (Daphnia magna, 48 h): 32 mg/l Experimental result, Supporting study
Heptane	EC 50 (Daphnia magna, 48 h): 1.5 mg/l Experimental result, Key study
Naphtha (petroleum), hydrotreated light	EC 50 (Daphnia magna, 48 h): 4.5 mg/l Experimental result, Key study

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Components:

Distillates (petroleum), light distillate hydrotreating process, low-boiling	NOAEL (Pimephales promelas): 2.6 mg/l Experimental result, Supporting study
White mineral oil (petroleum)	NOAEL (Oncorhynchus mykiss): $\geq 1,000$ mg/l QSAR QSAR, Supporting study
Ethanol	NOAEL (Oryzias latipes): 7,900 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study
Heptane	NOAEL (Oncorhynchus mykiss): 1.284 mg/l QSAR QSAR, Key study

Naphtha (petroleum), hydrotreated light NOAEL (Daphnia magna): 2.6 mg/l Other, Key study

Aquatic Invertebrates

Product: No data available.

Components:

Distillates (petroleum), light distillate hydrotreating process, low-boiling NOAEL (Daphnia magna): 2.6 mg/l Experimental result, Key study

Naphtha (petroleum), light alkylate NOAEL (Daphnia magna): 2.6 mg/l Experimental result, Key study

White mineral oil (petroleum) NOAEL (Daphnia magna): >= 1,000 mg/l QSAR QSAR, Supporting study

Ethanol LC 50 (Daphnia magna): 454 mg/l Experimental result, Key study
NOAEL (Daphnia magna): 9.6 mg/l Experimental result, Key study

Heptane NOAEL (Daphnia magna): 0.17 mg/l Read-across based on grouping of substances (category approach), Key study
EC 50 (Daphnia magna): 0.23 mg/l Read-across based on grouping of substances (category approach), Key study

Heptane, branched, cyclic and linear NOEC : < 1 mg/l estimation

Naphtha (petroleum), hydrotreated light EC 50 (Daphnia magna): 10 mg/l Experimental result, Key study

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

Components:

Distillates (petroleum), light distillate hydrotreating process, low-boiling 90.35 % (28 d) Detected in water. Experimental result, Supporting study

Naphtha (petroleum), light alkylate 90.35 % (28 d) Detected in water. Experimental result, Supporting study

Butane 100 % (385.5 h) Detected in water. Experimental result, Key study

White mineral oil (petroleum) 31 % (28 d) Detected in water. Read-across from supporting substance (structural analogue or surrogate), Supporting study

Petrolatum 31 % (28 d) Detected in water. Read-across from supporting substance (structural analogue or surrogate), Supporting study

Ethanol 95 % Detected in water. Experimental result, Key study

Propane 100 % (385.5 h) Detected in water. Experimental result, Key study
50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study

Solvent naphtha (petroleum), light aliph. 90.35 % (28 d) Detected in water. Experimental result, Supporting study

Heptane 70 % Detected in water. Experimental result, Key study

Naphtha (petroleum), hydrotreated light 90.35 % (28 d) Detected in water. Experimental result, Supporting study

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Components:

Distillates (petroleum), light distillate hydrotreating process, low-boiling Bioconcentration Factor (BCF): 10 - 2,500 Aquatic sediment Estimated by calculation, Key study

Naphtha (petroleum), light alkylate Bioconcentration Factor (BCF): 10 - 2,500 Aquatic sediment Estimated by calculation, Key study

Ethanol Cyprinus carpio, Bioconcentration Factor (BCF): 4.5 Aquatic sediment Read-across from supporting substance (structural analogue or surrogate), Supporting study

Solvent naphtha (petroleum), light aliph. Bioconcentration Factor (BCF): 10 - 2,500 Aquatic sediment Estimated by calculation, Key study

Heptane Bioconcentration Factor (BCF): 552 Aquatic sediment Estimated by calculation, Key study

Naphtha (petroleum), hydrotreated light Bioconcentration Factor (BCF): 10 - 2,500 Aquatic sediment Estimated by calculation, Key study

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Components:

Naphtha (petroleum), hydrotreated light Log Kow: > 2.4 - < 5.7 23 °C Yes Experimental result, Key study

Mobility in soil: No data available.

Components:

Distillates (petroleum), light distillate hydrotreating process, low-boiling	No data available.
Naphtha (petroleum), light alkylate	No data available.
Butane	No data available.
White mineral oil (petroleum)	No data available.
Petrolatum	No data available.
Ethanol	No data available.
Propane	No data available.
Solvent naphtha (petroleum), light aliph.	No data available.
Heptane	No data available.
Heptane, branched, cyclic and linear	No data available.
Naphtha (petroleum), hydrotreated light	No data available.

Other adverse effects: Toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions: Discharge, treatment, or disposal may be subject to national, state, or local laws.

Contaminated Packaging: No data available.

14. Transport information

DOT

UN Number:	UN 1950
UN Proper Shipping Name:	Aerosols, flammable
Transport Hazard Class(es)	
Class:	2.1
Label(s):	–
EmS No.:	
Packing Group:	–
Special precautions for user:	Not regulated.

IATA

UN Number:	UN 1950
UN Proper Shipping Name:	Aerosols, flammable
Transport Hazard Class(es):	
Class:	2.1
Label(s):	–
Packing Group:	–
Special precautions for user:	Not regulated.
Other information	
Passenger and cargo aircraft:	Allowed. 203
Cargo aircraft only:	Allowed. 203

IMDG

UN Number:	UN 1950
UN Proper Shipping Name:	Aerosols, flammable
Transport Hazard Class(es)	
Class:	2
Label(s):	–
EmS No.:	
Packing Group:	–
Special precautions for user:	Not regulated.

15. Regulatory information

US Federal Regulations

Restrictions on use: Not known.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Benzene	Flammability Cancer Aspiration Eye Blood Skin Respiratory tract irritation Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>
UNLISTED HAZARDOUS WASTES CHARACTERISTIC OF IGNITABILITY RCRA HAZARDOUS WASTE NO. D001 BENZENE, METHYL- BENZENE BENZENE, 1-METHYLETHYL- CUMENE ETHYLBENZENE

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Flammable (gases, aerosols, liquids, or solids), Aspiration Hazard

US. EPCRA (SARA Title III) Section 304 Extremely Hazardous Substances Reporting Quantities and the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substances

None present or none present in regulated quantities.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.65) - Supplier Notification Required

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

US State Regulations

US. California Proposition 65

For more information go to www.P65Warnings.ca.gov.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Distillates (petroleum), light distillate hydrotreating process, low-boiling
Butane
White mineral oil (petroleum)
Petrolatum
Ethanol
Propane
Solvent naphtha (petroleum), light aliph.
Naphtha (petroleum), hydrotreated light
Heptane

US. Massachusetts RTK - Substance List

Chemical Identity

Distillates, Petroleum, Hydrotreated Light Naphthenic
Distillates (petroleum), hydrotreated light paraffinic

Distillates (petroleum), solvent-dewaxed light paraffinic
Benzene

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Distillates (petroleum), light distillate hydrotreating process, low-boiling
Butane
White mineral oil (petroleum)
Petrolatum
Ethanol
Propane
Solvent naphtha (petroleum), light aliph.
Naphtha (petroleum), hydrotreated light
Heptane

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

Inventory Status:

Australia AICS	On or in compliance with the inventory
Canada DSL Inventory List	On or in compliance with the inventory
Canada NDSL Inventory	Not in compliance with the inventory.
Ontario Inventory	Not in compliance with the inventory.
China Inv. Existing Chemical Substances	Not in compliance with the inventory.
Japan (ENCS) List	Not in compliance with the inventory.
Japan ISHL Listing	Not in compliance with the inventory.
Japan Pharmacopoeia Listing	Not in compliance with the inventory.
Korea Existing Chemicals Inv. (KECI)	On or in compliance with the inventory
Mexico INSQ	Not in compliance with the inventory.
New Zealand Inventory of Chemicals	On or in compliance with the inventory
Philippines PICCS	On or in compliance with the inventory
Taiwan Chemical Substance Inventory	On or in compliance with the inventory
US TSCA Inventory	On or in compliance with the inventory
EINECS, ELINCS or NLP	Not in compliance with the inventory.

16. Other information, including date of preparation or last revision

Issue Date: 11/18/2020

Revision Information: No data available.

Version #: 1.0

Further Information: No data available.

Disclaimer: This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.